



# Easy Flex<sup>®</sup>

XP3018 - 50cm wide

## STEP BY STEP

### Step 1

Cut your design in mirror image **Film blade required (90 - 100gf)**

### Step 2

Weed away any excess material

### Step 3

Place transfer face down onto the garment with the transparent backing on top and press for 10 seconds at 150°C. (Low Temp Press for 20 seconds at 120°C)

**LOW TEMPERATURE NOT SUITABLE FOR FLUORESCENT**

### Step 4

Remove the transparent backing cold

## DURABILITY

90°C

## MICRONS

105-125µ

## FINISH

Gloss

## TACK

Medium

## PEEL

Cold

## PU or PVC

PVC

## PRODUCT INFORMATION

SIZE: 50cm wide x 5 & 20m rolls  
CUTTING FORCE: 90 - 100gf (Film Blade)  
TRANSFER LAYERING: Yes (excluding metallics and fluorescents)

**PLEASE NOTE:** Re-press for 5 seconds after the removal of the backing when multi transfer layering. (When overlaying ensure that only 2mm of the bottom layer is overlaid by the top layer.)

## SUITABLE FOR

- ▶ Cotton
- ▶ Polyester
- ▶ Polyester/Cotton

Uncoated garments only

## TRANSFER SETTINGS

TIME	10 seconds (low temp - 20 seconds)
TEMPERATURE	150°C (Football shirts 140°C / low temp = 120°C) <b>LOW TEMP NOT SUITABLE FOR FLUORESCENTS</b>
PRESSURE	Medium
PEEL	Cold

## CARE INFORMATION

- ▶ Up to 90°C (Up to 40°C inside out when transfer layering)
- ▶ Can be dry cleaned
- ▶ Can be tumble dried
- ▶ **Do not** iron

**PLEASE NOTE:** A4 samples are available free of charge upon request, for larger samples 1m rolls are available for purchase.

**PLEASE NOTE:** The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Easy Flex shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Easy Flex has been tested using Kustom Kit garments, when applying to other garment brands results may vary, testing prior to purchase is recommended.