



Solvent Light

XP3025 - 50cm wide

XP3138 - 75cm wide

STEP BY STEP

Step 1

Print your design on to the smooth matt side (**Mirror image**) **Film blade required (60 - 80gf)**

Step 2

Weed away any excess material

Step 3

Place transfer face down onto the garment with the polyester backing on top and press for 15 seconds at 165°C

Step 4

Remove the polyester backing cold

PRINT SETTINGS

Media Type

TTRH

Colour Management

Pre-Press Europe

Print Heater

35°C

Dryer

45°C

Drying time

No drying time required

DURABILITY

60°C
Inside Out

MICRONS

75µ

FINISH

Matt

PEEL

Cold

PU or PVC

PU

ADVISORIES

- ▶ Solvent Light is not recommended for small detail

PRODUCT INFORMATION

SIZE: 50cm & 75cm wide x 25m rolls
CUTTING FORCE: 60 - 80gf (Film Blade)
APPLICATION TAPE: No

SUITABLE FOR - White garments only

- ▶ Cotton
- ▶ Polyester
- ▶ Polyester/Cotton

Uncoated garments only

TRANSFER SETTINGS

TIME	15 seconds
TEMPERATURE	165°C
PRESSURE	Medium
PEEL	Cold

CARE INFORMATION

- ▶ Up to 60°C inside out
- ▶ **Do not** dry clean
- ▶ Can be tumble dried
- ▶ **Do not** iron

PLEASE NOTE: 1m samples are available free of charge upon request.

PLEASE NOTE: The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Solvent Light shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Solvent Light has been tested using Kustom Kit garments, when applying to other garment brands results may vary, testing prior to purchase is recommended.

Oakridge Park, Trent Lane
Castle Donington, Derby
DE74 2PY

Phone: 01332 855 085
Web: www.xpres.co.uk
E-mail: sales@xpres.co.uk
Support: www.xprestechnical.co.uk