



Easy Print

XP3030 - 50cm wide x 10m roll
XP3031 - 50cm wide x 20m roll
XP3033 - 75cm wide x 10m roll
XP3034 - 75cm wide x 20m roll



Class 2

STEP BY STEP

Step 1

Print your design on the smooth matt side (**Do not mirror image**) **Film blade required (90 - 100gf)**

Step 2

Weed away any excess material. If using application tape cover with Transfer application tape using a squeegee to remove any air bubbles

Step 3

Place transfer face up onto the garment (application tape on top) cover with a silicone sheet and press for 15 seconds at 150°C

Step 4

Remove the silicone sheet cold or peel hot when using application tape

PRINT SETTINGS

Media Type

Generic Vinyl I

Colour Management

Max Impact

Print Heater

45°C

Dryer

50°C

Drying time

4 hours

DURABILITY

60°C
inside out

MICRONS

160µ

FINISH

Matt

PEEL

Hot or Cold

PU or PVC

PVC

PRODUCT INFORMATION

SIZE: 50cm & 75cm wide x 10 & 20m rolls
CUTTING FORCE: 90 - 100gf (Film Blade)
APPLICATION TAPE: Transfer application tape

SUITABLE FOR

- ▶ Cotton
- ▶ Polyester
- ▶ Polyester/Cotton

Uncoated garments only

TRANSFER SETTINGS

TIME	15 seconds
TEMPERATURE	150°C
PRESSURE	Medium
PEEL	Hot or Cold

CARE INFORMATION

- ▶ Up to 60°C inside out
- ▶ **Do not** dry clean
- ▶ Can be tumble dried
- ▶ Can be ironed inside out

PLEASE NOTE: 1m samples are available free of charge upon request.

PLEASE NOTE: The sellers and manufacturers maximum obligation shall be to replace any product that has been proven to be defective. Neither the seller nor the manufacturer of Easy Print shall be liable for any injury direct or consequential, arising out of the use of, or inability to use this range. Easy Print has been tested using Kustom Kit garments, when applying to other garment brands results may vary, testing prior to purchase is recommended.

Oakridge Park, Trent Lane
Castle Donington, Derby
DE74 2PY

Phone: 01332 855 085
Web: www.xpres.co.uk
E-mail: sales@xpres.co.uk
Support: www.xprestechnical.co.uk